



HL 20-125

Plaatdikte	0,63 mm
Gewicht per m ²	6,30 kg/m ²
Plaatdikte	0,70 mm
Gewicht per m ²	7,00 kg/m ²

Coating			
Zichtzijde	Graniet	35 µm	glad
	Pacific	25 µm	glad
	Plastisol	200 µm	leer
	Pvdf	25 µm	glad

Potdekselprofiel HL 20-125

Doorbuiging $f_{max} = 1/200$

Oplegbreedte 60 mm

Toelaatbare overspanningen in mm

Gebied		I			II			III		
Aantal Velden	Dikte	Hoogte			9 m+	15 m+	30 m+	9 m+	15 m+	30 m+
Δ-Δ	0,63	1490	1420	1340	1580	1490	1400	1680	1580	1470
	0,70	1540	1460	1380	1630	1540	1440	1730	1630	1520
Δ-Δ-Δ	0,63	1930	1840	1730	2050	1940	1810	2180	2050	1910
	0,70	1990	1900	1790	2120	2000	1870	2250	2120	1970
Δ-Δ-Δ-Δ	0,63	1790	1700	1600	1900	1800	1680	2030	1910	1770
	0,70	1850	1760	1660	1970	1860	1740	2100	1970	1830

WERKCON
metal profiles

