



HL 40-500 NT

Plaatdikte	0,70 mm
Gewicht per m ²	6,85 kg/m ²
Plaatdikte	0,88 mm
Gewicht per m ²	8,80 kg/m ²

Coating			
Zichtzijde	Graniet	35 µm	glad
	Pacific	25 µm	glad
	Plastisol	200 µm	leer
	Pvdf	25 µm	glad

Potdekselprofiel HL 40-500 NT

Doorbuiging $f_{max} = 1/200$

Oplegbreedte 60 mm

Toelaatbare overspanningen in mm

Gebied		I			II			III		
Aantal Velden	Dikte	Hoogte			9 m+	15 m+	30 m+	9 m+	15 m+	30 m+
Δ ⁻ Δ	0,70	2400	2250	2150	2500	2400	2250	2700	2550	2350
	0,88	2580	2460	2310	2740	2590	2420	2920	2750	2550
Δ ⁻ Δ ⁻ Δ	0,70	3150	2950	2650	3350	3150	2850	3550	3350	3100
	0,88	3390	3230	3010	3610	4310	3180	3850	3610	3360
Δ ⁻ Δ ⁻ Δ ⁻ Δ	0,70	2900	2750	2600	3100	2900	2700	3300	3100	2850
	0,88	3150	3000	2820	3350	3160	2950	3570	3360	3120

WERKCON
metal profiles

